



## FX10+

### Pen Style Visual Fault Locator

#### Key Features

- Small pen size for field applications
- Simple operation
- CW and Pulsed operation
- Rugged and Weatherproof
- Lightweight anodized aluminum construction
- Durable dust cap to protect optical interface
- IEC 60825-1 Laser safety rating
  - Class 2 for 1 mW version (up to 5km)
  - Class 2M for 10 mW version (up to 10km)
- Low battery indication
- Accessories include (2) AA alkaline batteries and carrying pouch with wrist strap

#### Specifications\*

- Wavelength: 650 nm  $\pm$  10 nm
- Emitter type: FP-LD
- Output power: 1 mW or 10 mW models available
- Optical Connector: 2.5 mm universal; optional FC to universal 1.25 mm converter
- Operating modes: CW and Pulse
- Pulse frequency: 2 Hz - 3 Hz
- Power Supply: 2 Alkaline AA
- Operating time (Reputable Alkaline battery types):
  - 650 nm @ 1 mW 80 hours @ 10 mW 15 hours
- Operating temperature: -10°C to +45°C
- Storage temperature: -40°C to +70°C
- Size: 22 mm x 22 mm x 222 mm
- Weight (without batteries): 90 g or 0.20 lb
- CE compliance as per IEC 61326

*\*Notes:*

1. All specifications are valid at 23°C  $\pm$  2°C (73.4°F  $\pm$  3.6°F)
2. Output power using 50/125  $\mu$ m fiber

For more information



**dhs ELMEA tools GmbH**

Carl-Zeiss-Straße 43  
63322 Rödermark / Germany  
fon + 49 6074 / 91 99 08 - 0  
fax + 49 6074 / 91 96 747  
web [www.dhs-tools.de](http://www.dhs-tools.de)  
mail [info@dhs-tools.de](mailto:info@dhs-tools.de)

© 2019 VeEX Inc. All rights reserved.

VeEX is a registered trademark of VeEX Inc. The information contained in this document is accurate. However, we reserve the right to change any contents at any time without notice. We accept no responsibility for any errors or omissions. In case of discrepancy, the web version takes precedence over any printed literature.

D05-00-136P D00 2019/10