

FX10+

Pen Style Visual Fault Locator

Key Features

- Small pen size for field applications
- Simple operation
- CW and pulsed operation
- Rugged and weatherproof
- Lightweight anodized aluminum construction
- Durable dust cap to protect optical interface
- Class 2 IEC 60825 laser safety rating
- Low battery indication
- Accessories include (2) AA alkaline batteries and carrying pouch with wrist strap

Specifications[1]

- Wavelength: 650 nm ± 10 nm
- Emitter type: FP-LD
- Output power: 1 mW
- Optical Connector: 2.5 mm universal; optional FC to universal 1.25 mm converter
- Operating modes: CW and Pulse
- Pulse frequency: 2 Hz - 3 Hz
- Power Supply: 2 Alkaline AA
- Operating time (reputable alkaline battery types): 650 nm @ 1 mW 80 hours @ 10 mW 15 hours
- Operating temperature: -10˚C to +50˚C
- Storage temperature: -40˚C to +70˚C
- Size: 22 mm x 22 mm x 222 mm
- Weight (without batteries): 90 g or 0.20 lb
- CE compliance as per IEC 61326

Notes
1. Depends on fiber type, fiber loss, ambient light, and cable jacket type
2. All specifications are valid at 23˚C ± 2˚C (73.4˚F ± 3.6˚F)
3. Output power using 50/125 µm fiber

The Verification Experts

VeEX Inc.
2827 Lakeview Court
Fremont, CA 94538 USA
Tel: +1.510.651.0500
Fax: +1.510.651.0505
www.veexinc.com
customercare@veexinc.com

© 2024 VeEX Inc. All rights reserved.
VeEX is a registered trademark of VeEX Inc. The information contained in this document is accurate. However, we reserve the right to change any contents at any time without notice. We accept no responsibility for any errors or omissions. In case of discrepancy, the web version takes precedence over any printed literature.
D05-00-136P E02 2024/04